



## Safety Data Sheet

Material Name: Styrenated Phenol  
NEVILLAC® 5° XL Resin

### \*\*\*Section 1 – PRODUCT IDENTIFICATION\*\*\*

**Material Name:**  
Styrenated Phenol

**Trade Name:**  
NEVILLAC® 5°XL Resin

#### **Recommended Uses of Product and Restrictions**

Identified Uses: Adhesives, coatings, rubber  
Uses Advised Against: None Known

#### **Manufacturer Information**

Neville Chemical Company  
2800 Neville Road  
Pittsburgh, PA 15225-1496  
Phone:412-331-4200  
Emergency Phone #: 412-331-4200 or CHEMTREC at 800-424-9300  
Fax:412-777-4234

### \*\*\*Section 2 - HAZARD(S) IDENTIFICATION\*\*\*

#### **Classification in accordance with Schedule 1 of Hazardous Products Regulations (HPR) (SOR/2015-17)**

Skin Corrosion/Irritation - Category 2  
Skin Sensitization - Category 1A  
Hazardous to the Aquatic Environment - Chronic - Category 3

#### **GHS Label Elements**

##### **Symbol(s)**



##### **Signal Word**

Warning

##### **Hazard Statement(s)**

Causes skin irritation.  
May cause an allergic skin reaction.  
Harmful to aquatic life with long lasting effects.

# Safety Data Sheet

Material Name: Styrenated Phenol  
NEVILLAC® 5°XL Resin

## Precautionary Statement(s)

### Prevention

Use only outdoors or in a well-ventilated area.  
Wear protective gloves/protective clothing/eye protection/face protection.  
Avoid breathing dust/fume/gas/mist/vapors/spray.  
Wash thoroughly after handling.  
Contaminated work clothing must not be allowed out of the workplace.  
Avoid release to the environment

### Response

IF ON SKIN: Wash with plenty of soap and water.  
If skin irritation or rash occurs: Get medical advice/attention.  
Take off contaminated clothing and wash before reuse.

### Storage

None needed according to classification criteria

### Disposal

Dispose of contents/container in accordance with local/regional/national/international regulations

### Hazard(s) Not Otherwise Classified

Contact with molten (hot) material may cause thermal burns.

## \* \* \*Section 3 - COMPOSITION / INFORMATION ON INGREDIENTS\* \* \*

CAS	Component	Percentage
61788-44-1	Phenol, styrenated (EC Number 262-975-0)	>99.9%
108-95-2	Phenol (EC Number 203-632-7)	<0.1%

### Contaminants:

<0.1% free untreated phenol remains in the product

# Safety Data Sheet

Material Name: Styrenated Phenol  
NEVILLAC® 5°XL Resin

## \*\*\*Section 4 - FIRST-AID MEASURES\*\*\*

### Description of Necessary Measures

#### Inhalation

Supply fresh air. Consult a doctor in case of complaints.  
If adverse effects occur, remove to uncontaminated area. Give artificial respiration if not breathing. Get immediate medical attention.

#### Skin Contact

Wash skin with soap and water thoroughly while removing contaminated clothing and shoes.

#### Eye Contact

Flush eyes with plenty of water for at least 15 minutes. Then consult a doctor.

#### Ingestion

Get medical attention

### Most Important Symptoms/Effects

#### Acute

Mild skin irritation.

#### Delayed

No information on significant adverse effects.

### Indication of Immediate Medical Attention and Special Treatment Needed, If Needed

Provide general supportive measures and treat symptomatically.

## \*\*\*Section 5 - FIRE-FIGHTING MEASURES\*\*\*

### Suitable Extinguishing Media

Dry chemical, carbon dioxide, foam, water spray

### Unsuitable Extinguishing Media

Do not use high-pressure water streams.

# Safety Data Sheet

Material Name: Styrenated Phenol  
NEVILLAC® 5°XL Resin

## Special Hazard Arising from the Chemical

Combustible liquid and vapor. May burn if exposed to surrounding fire. When heated above its boiling point, may generate vapors that may ignite in air and a source of ignition. Vapors are heavier than air and can collect in low areas; vapors can travel to an ignition source and flash back.

**Combustion:** oxides of carbon, carbon monoxide, hydrocarbons.

## Fire Fighting Measures

Keep away from sources of ignition - No smoking. Avoid inhalation of material or combustion by-products. Move material from fire area if it can be done without risk. Use extinguishing agents appropriate for surrounding fire. Dike for later disposal. Stay upwind and keep out of low areas.

## Special Protective Equipment and Precautions for Firefighters

Wear full protective fire fighting gear including self contained breathing apparatus (SCBA) for protection against possible exposure.

<b>* * *Section 6 - ACCIDENTAL RELEASE MEASURES* * *</b>
--

## Personal Precautions, Protective Equipment and Emergency Procedures

Wear appropriate personal protective equipment recommended in Section 8 of the MSDS. Keep unnecessary people away, isolate hazard area and deny entry. Avoid contact with skin and eyes. Avoid release to the environment. Only personnel trained for the hazards of this material should perform clean up and disposal.

## Methods and Materials for Containment and Cleaning Up

Use non-sparking tools and equipment. Keep unnecessary people away, isolate hazard area and deny entry. Absorb with sand or other non-combustible material. Keep out of water supplies, sewers and soil. Collect spilled material in appropriate container for disposal. In case of spillage, stop the flow of material and block any potential routes to water systems.

# Safety Data Sheet

Material Name: Styrenated Phenol  
NEVILLAC® 5°XL Resin

## \*\*\*Section 7 - HANDLING AND STORAGE\*\*\*

### Precautions for Safe Handling

Keep away from heat, sparks, open flame, hot surfaces & direct sun light. Wear protective gloves and eye/face protection. Keep away from all ignition sources. Avoid contact with skin and eyes. Always wear recommended personal protective clothing and equipment.- See Section 8. Take precautionary measures against static discharge. Dissipate static electricity during transfer by earthing (grounding and bonding) containers and equipment. Do not breathe vapor or mist.

### Conditions for Safe Storage, including any Incompatibilities

Store in a cool, dry place. Store in a well-ventilated area. Avoid contact with molten material. Keep separated from incompatible substances. Keep container tightly closed. Empty containers may contain product residue. Do not reuse empty containers without commercial cleaning or reconditioning. Store and handle in accordance with all current regulations and standards.

### Incompatible Materials

oxidizing materials, combustible materials

## \*\*\*Section 8 - EXPOSURE CONTROLS / PERSONAL PROTECTION\*\*\*

### Component Exposure Limits

Components with limit values that require monitoring at the workplace:	
108-95-2	Phenol
PEL (USA)	Long-term value: 19 mg/m <sup>3</sup> , 5 ppm, Skin
REL (USA)	Short-term value: C60* mg/m <sup>3</sup> , C 15.6* ppm Long-term value: 19 mg/m <sup>3</sup> , 5 ppm *15-0min; Skin
TLV (USA)	Long-term value: 19 mg/m <sup>3</sup> , 5 oom. Skin: BEI
Ingredients with biological limit values:	
108-95-2	Phenol
BEI (USA)	250 mg/g creatinine. Medium: urine / Time: end of shift Parameter: Phenol with hydrolysis (background, nonspecific)

# Safety Data Sheet

Material Name: Styrenated Phenol  
NEVILLAC® 5°XL Resin

## Appropriate Engineering Controls

Provide a local exhaust ventilation system. Ventilation equipment should be explosion-resistant if explosive concentrations of material are present. It is recommended that all vapor control equipment such as local exhaust ventilation and material transport systems involved in handling of these product contain explosion relief vents or an explosion suppression system or an oxygen-deficient environment. Ensure that vapor-handling systems (such as exhaust ducts, vessels, and processing equipment) are designed in a manner to prevent the escape of vapors into the work area (i.e., there is no leakage from the equipment). Use only appropriately classified electrical equipment and powered industrial trucks.

## Individual Protection Measures, such as Personal Protective Equipment

### General protective and hygienic measures:

Wash hands before breaks and at the end of work.

### Eyes/Face Protection

Wear splash resistant safety goggles with a face shield.

### Skin Protection

Wear appropriate chemical resistant clothing. Include boots and a protective suit if needed.

### Glove Recommendations

Wear appropriate chemical resistant gloves. Recommended material: rubber, neoprene.  
The resistance of the glove material should be checked prior to the application.

### Respiratory Protection

A NIOSH approved respirator with organic vapor cartridges and N95 filters may be permissible under certain circumstances where airborne concentrations are expected to exceed exposure limits, or when symptoms have been observed that are indicative of overexposure.

# Safety Data Sheet

Material Name: Styrenated Phenol  
NEVILLAC® 5°XL Resin

<b>***Section 9 - PHYSICAL AND CHEMICAL PROPERTIES***</b>
---

<b>Physical State:</b>	Semi Viscous Liquid	<b>Vapor Density (air = 1):</b>	Not available
<b>Appearance:</b>	Fluid	<b>Evaporation Rate (water = 1) :</b>	<1
<b>Color:</b>	Light Yellow	<b>pH:</b>	Not available
<b>Odor:</b>	Phenolic Like	<b>Boiling Point:</b>	232°C.
<b>Odor Threshold:</b>	Not available	<b>Boiling Point Range:</b>	Not Available
<b>Softening Point:</b>	Not Applicable	<b>Decomposition Temperature:</b>	Not available
<b>Melting Point:</b>	Not available	<b>Vapor Pressure:</b>	25 Pa at 68°F. 171.22 Pa @ 122°F.
<b>Freezing Point:</b>	Not available	<b>KOC:</b>	Not available
<b>Specific Gravity (water = 1):</b>	1.07 @ 25°C	<b>Log KOW: (n-octanol/water)</b>	DSP: 6.24 TSP: 7.77
<b>Molecular Weight (Mn):</b>	Not available	<b>Water Solubility:</b>	DSP: 665ug/l – TSP: 7.1ug/l
<b>VOC:</b>	Not available	<b>Coeff. Water/Oil Dist:</b>	Not available
<b>Flash Point:</b>	>365 °F	<b>Relative Density:</b>	Not available
<b>OSHA Flammability Class:</b>	Not classified	<b>Viscosity, Brookfield, cps.:</b>	4,700 ± 2,400 25°C. 250 @ 50° C.
<b>Minimum Explosive Concentration:</b>	Not available	<b>Taste:</b>	Not available
<b>KSt-value (bar x m/s):</b>	Not available	<b>LEL:</b>	Not available
<b>Auto Ignition Temperature:</b>	Not available	<b>UEL:</b>	Not available

<b>***Section 10 - STABILITY AND REACTIVITY***</b>
--

**Reactivity**

None known.

**Chemical Stability**

Stable at normal temperatures and pressure.

**Possibility of Hazardous Reactions**

Hazardous polymerization will not occur.

**Conditions to Avoid**

Avoid heat, flames, sparks and other sources of ignition.

# Safety Data Sheet

Material Name: Styrenated Phenol  
NEVILLAC® 5°XL Resin

## Incompatible Materials

Oxidizing materials, combustible materials

## Hazardous decomposition products

Oxides of carbon, carbon monoxide, hydrocarbons, phenolic type compounds

**Combustion:** oxides of carbon, carbon monoxide, hydrocarbons.

## \* \* \*Section 11 - TOXICOLOGICAL INFORMATION\* \* \*

### Acute and Chronic Toxicity

#### Acute toxicity:

LD/LC50 values that are relevant for classification:		
<b>61788-44-1 Phenol, styrenated</b>		
Oral	LD50	2,500 mg/kg (rat) (OECD 423)
<b>108-95-2 phenol</b>		
Oral	LD50	317 mg/kg (rat)
Dermal	LD50	850 mg/kg (rabbit)

### Information on Likely Routes of Exposure Inhalation

#### Inhalation:

No information on significant adverse effects.

#### Ingestion

No information on significant adverse effects.

#### Skin Contact

No information on significant adverse effects.

#### Eye Contact

No information on significant adverse effects.

#### Immediate Effects

No information on significant adverse effects.



# Safety Data Sheet

Material Name: Styrenated Phenol  
NEVILLAC® 5°XL Resin

## Delayed Effects

No information on significant adverse effects.

## Medical Conditions Aggravated by Exposure

No data available.

## Irritation/Corrosivity Data

No information on significant adverse effects.

## Respiratory Sensitization

No data available.

## Dermal Sensitization

No data available.

## Germ Cell Mutagenicity

No data available.

## Carcinogenicity

### Component Carcinogenicity

IARC (International Agency for Research on Cancer)		
108-95-2	phenol	3
100-42-5	Styrene	2B
100-41-4	Ethylbenzene	2B

## Reproductive Toxicity

No data available.

## Specific Target Organ Toxicity - Single Exposure

No data available.

## Specific Target Organ Toxicity - Repeated Exposure

No data available.

## Aspiration hazard

No data available.

# Safety Data Sheet

Material Name: Styrenated Phenol  
NEVILLAC® 5°XL Resin

## \*\*\*Section 12 - ECOLOGICAL INFORMATION\*\*\*

### Ecotoxicity

Harmful to aquatic life with lasting effects.

### Component Analysis - Aquatic Toxicity

Aquatic Toxicity	
<b>61788-44-1 Phenol, styrenated</b>	
EC50 (48 h)	DSP: >0.249 mg/l (daphnia)
EC50 (72 h)	DSP: 0.326 mg/l (algae)

### Persistence and Degradability

Not easily biodegradable.

### Other Information:

21 days-NOEC-Reproduction, Daphnia Magna:

DSP: 115ug/l. TSP: 35ug/l: Absence of long term effect at the limit of water solubility

72h-NOEC-Algae:

DSP: 140ug/l, TSP: 5.15ug/l. Absence of long term effect at the limit of water solubility

### Bioaccumulation

No information available for the product.

### Mobility in Soil

No information available for the product.

### General Notes:

Do not allow product to reach ground water, water course or sewage system. Toxic for aquatic organisms.

### Results of PBT and vPvB assessment

PBT: Not applicable

vPvB: Not applicable

# Safety Data Sheet

Material Name: Styrenated Phenol  
NEVILLAC® 5°XL Resin

## Other Adverse Effects:

No information available for this product

## \*\*\*Section 13 - DISPOSAL CONSIDERATIONS\*\*\*

### Disposal Methods

Dispose of contents/container in accordance with local/regional/national/international regulations.

### Disposal of Contaminated Packaging

Dispose of waste material according to Local, State, Federal, and Provincial Environmental Regulations.

## \*\*\*Section 14 - TRANSPORT INFORMATION\*\*\*

### US DOT Information

**Shipping Name:** Not regulated for transport

**UN/NA #:** Not Regulated

**Not DOT Hazardous in non-bulk packaging (Drums / Pails)**

# Safety Data Sheet

Material Name: Styrenated Phenol  
NEVILLAC® 5°XL Resin

## Transport of dangerous goods by sea:

With regard to IMDG 40-20:

- |             |   |  |
|-------------|---|--|
| <b>14.1</b> | <b>UN number</b>  |  |
| <b>14.2</b> | <b>UN proper shipping name:</b>   | ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Phenol, styrenated) |
| <b>14.3</b> | <b>Transport hazard class(es):</b>  | 9  |
|             | Labels:   | 9  |
| <b>14.4</b> | <b>Packing group, if applicable:</b>  | III  |
| <b>14.5</b> | <b>Marine pollutant:</b>  | Yes  |
| <b>14.6</b> | <b>Special precautions which a user needs to be aware of, or needs to comply with, in connection with transport or conveyance either within or outside their premises</b> |  |
|             | Special regulations:  | 335, 969, 274  |
|             | EmS Codes:  | F-A, S-F   |
|             | Physico-Chemical properties:  | see section 9  |
|             | Limited quantities:   | 5 L  |
|             | Segregation group:  | Non-applicable   |
| <b>14.7</b> | <b>Transport in bulk (according to Annex II of MARPOL 73/78 and the IBC Code):</b>  | Non-applicable   |

## Transport of dangerous goods by air:

With regard to IATA/ICAO 2022:

- |             |   |  |
|-------------|---|--|
| <b>14.1</b> | <b>UN number:</b>   | UN3082   |
| <b>14.2</b> | <b>UN proper shipping name:</b>   | ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Phenol, styrenated) |
| <b>14.3</b> | <b>Transport hazard class(es):</b>  | 9  |
|             | Labels:   | 9  |
| <b>14.4</b> | <b>Packing group, if applicable:</b>  | III  |
| <b>14.5</b> | <b>Marine pollutant:</b>  | Yes  |
| <b>14.6</b> | <b>Special precautions which a user needs to be aware of, or needs to comply with, in Connection with transport or conveyance either within or outside their premises</b> |  |
|             | Physico-Chemical properties:  | see section 9  |
| <b>14.7</b> | <b>Transport in bulk (according to Annex II of MARPOL 73/78 and the IBC Code):</b>  | Non-applicable   |

# Safety Data Sheet

Material Name: Styrenated Phenol  
NEVILLAC® 5°XL Resin

**\*\*\*Section 15 - REGULATORY INFORMATION\*\*\***

**U.S. Federal Regulations**

Safety, health and environmental regulations/legislation specific for the substance or mixture

**Sara**

<b>Section 355 (extremely hazardous substances) &gt;0.1%</b>	
108-95-2	Phenol
<b>Section 313 (Specific toxic chemical listings) with De Minimis Limit 0.1%</b>	
108-95-2	Phenol
<b>TSCA (Toxic Substances Control Act):</b>	
Substance is listed.	
<b>Carcinogenic categories</b>	
<b>EPA (Environmental Protection Agency) &gt;0.1%</b>	
108-95-2	Phenol
<b>NIOSH-Ca (National Institute for Occupational Safety and Health) &gt;0.1%</b>	
Substance is not listed	
<b>OSHA-Ca (Occupational Safety &amp; Health Administration) &gt;0.1%</b>	
Substance is not listed	

**Canada Regulations**

This product has been classified in accordance with the criteria of the Controlled Products Regulations (CPR) and the SDS contains all of the information required by the CPR.

**Canadian WHMIS Ingredient Disclosure List (IDL)**

Components of this material have been checked against the Canadian WHMIS Ingredients Disclosure List. The List is composed of chemicals which must be identified on SDSs if they are included in products which meet WHMIS criteria specified in the Controlled Products Regulations and are present above the threshold limits listed on the IDL:

**Canadian WHMIS Information**

WHMIS CLASSIFICATION: D2

**Component Analysis - Inventory**

Component	CAS	US	CA	EU	AU	PH	JP	KR	CN	NZ
Phenol, styrenated	61788-44-1	Yes	Yes	EIN	Yes	Yes	Yes	Yes	Yes	Yes

# Safety Data Sheet

Material Name: Styrenated Phenol  
NEVILLAC® 5°XL Resin

## \*\*\*Section 16 - OTHER INFORMATION\*\*\*

**NFPA Ratings: Health: 2 Fire: 1 Reactivity: 0**

Hazard Scale: 0 = Minimal 1 = Slight 2 = Moderate 3 = Serious 4 = Severe

### HMIS RATINGS:

**Health: 2**

**Fire: 1**

**Reactivity: 0**

**Pers. Prot.: B Minimum**

Hazard Scale: 0 = Minimal 1 = Slight 2 = Moderate 3 = Serious 4 = Severe \* = Chronic hazard

### Key / Legend

ACGIH - American Conference of Governmental Industrial Hygienists; ADR - European Road Transport; AU - Australia; BOD - Biochemical Oxygen Demand; C - Celsius; CA - Canada; CAS - Chemical Abstracts Service; CERCLA - Comprehensive Environmental Response, Compensation, and Liability Act; CN - China; CPR - Controlled Products Regulations; DFG - Deutsche Forschungsgemeinschaft; DOT - Department of Transportation; DSL - Domestic Substances List; EEC - European Economic Community; EINECS - European Inventory of Existing Commercial Chemical Substances; EPA - Environmental Protection Agency; EU - European Union; F - Fahrenheit; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; ICAO - International Civil Aviation Organization; IDL - Ingredient Disclosure List; IMDG - International Maritime Dangerous Goods; JP - Japan; Kow - Octanol/water partition coefficient; KR - Korea; LEL - Lower Explosive Limit; LOLI - List Of Lists™ - ChemADVISOR's Regulatory Database; MAK - Maximum Concentration Value in the Workplace; MEL - Maximum Exposure Limits; NFPA - National Fire Protection Agency; NIOSH - National Institute for Occupational Safety and Health; NJTSR - New Jersey Trade Secret Registry; NTP - National Toxicology Program; NZ - New Zealand; OSHA - Occupational Safety and Health Administration; PH - Philippines; RCRA - Resource Conservation and Recovery Act; RID - European Rail Transport; RTECS - Registry of Toxic Effects of Chemical Substances®; SARA - Superfund Amendments and Reauthorization Act; STEL - Short-term Exposure Limit; TDG - Transportation of Dangerous Goods; TSCA - Toxic Substances Control Act; TWA - Time Weighted Average; UEL - Upper Explosive Limit; US - United States

### Other Information

Reasonable care has been taken in the preparation of this information; however, the manufacturer makes no warranty whatsoever including the warranty of merchantability, expressed or implied, with respect to this information.