



TECHNICAL DATA SHEET

Neville Chemical Company
2800 Neville Road
Pittsburgh, PA 15225-1496

Phone: 412-777-4210
E-Mail: support@nevchem.com
Internet: www.nevchem.com

NEVILLAC[®] 5° XL Resin

PRODUCT DESCRIPTION

NEVILLAC[®] 5° XL Resin is a low molecular weight styrenated phenolic liquid resin.

APPLICATIONS / END USES

- Epoxy Coatings/Adhesives
- Protective and Marine Coatings
- Industrial Maintenance Coatings

ATTRIBUTES / BENEFITS

- Efficiently Accelerate the Curing
- Light Color
- Provide Good Adhesion
- Provide Good Chemical Resistance

PROPERTIES

Property	Test Method	Typical Value	Specifications
Brookfield Viscosity, cps @ 25°C	ASTM D2196-86	1,500	1,500 ± 300
Gardner Color, Straight	ASTM D1544	2	5 Max.
Hydroxyl Number	ASTM E222	195	NA
Flash Point °F (COC)	Method N.601	> 320	NA
Specific Gravity @ 25°C	ASTM D891	1.08	NA
Appearance	Visual	Pale Yellow Liquid	NA

PACKAGING: NEVILLAC[®] 5° XL Resin is shipped in drums, 440 pounds net weight.

TSCA Status: Neville Chemical Company certifies that all components of this product are on the TSCA Inventory.