TECHNICAL DATA SHEET

VERSADIL® 100

PRODUCT DESCRIPTION

VERSADIL® 100 is a clear, light color liquid C5 aliphatic hydrocarbon resin/vegetable oil hybrid.

APPLICATIONS and END USES

- Exterior Wood Coating (Pigmented and Clear)
- High Solids architectural and General Maintenance Coatings

FEATURES and BENEFITS

- Significantly Lower VOC's
- Impedes Mildew Growth
- Resists UV Light
- Improves Penetration in Porous Substrates
- Augments Pigment and Filler Wetting
- Light Color

PROPERTIES

Property	Test Method	Typical Value	Specification
Brookfield Viscosity cps @ 25°C	ASTM D2196	650	600 ± 100
Gardner Color, Straight	ASTM D1544	4.5	7 Max
Flash Point, °F (COC)	ASTM D92	>300	N/A
Specific Gravity @ 25°C	ASTM D71	0.93	N/A

PACKAGING

400 lbs. (181.4 kg.) net weight steel drums / 4 drums per pallet

STORAGE CONDITIONS

Store in a cool, dry place. For best results, inside storage in a cool, dry place is recommended and keep at temperatures not exceeding 30°C.

SHELF LIFE

24 Months

The shelf life is a guide, not an absolute value. The product should be reanalyzed for critical application-specific properties near the end of the shelf life to determine if it meets specifications for use.

REGULATORY COMPLIANCE

Neville Chemical Company certifies that all components of this product are on the TSCA Inventory.

FDA STATUS

No information available.

Neville Chemical Company
2800 Neville Road
Pittsburgh, PA 15225-1496

412-777-4210 : Phone
support@nevchem.com : E-Mail
www.nevchem.com : Website

Revised: November 12, 2026